



Your Partner in Business

SUNRISE INDUSTRIAL EQUIPMENT & TRADING CO., LTD  
No.31, New Road No.5, Haiphong.



6005



## CPU-700A/B

### POLYURETHANE CPU-700A/B (High-strength Polyurethane Coating Agent)

**Packaging** CPU-700A(main agent) 5kg/CAN

**Unit :** CPU-700B(hardener) 20kg/CAN

#### Features


- Excellent long-term antirusting effects
- Excellent cohesion and adhesion
- Excellent insulation.
- Strong against gas, acid and alkaline chemicals
- Excellent shock-resistance and antiabrasion
- Excellent vibration resistance, water proofing and insect resistance.
- Beautiful appearance

#### Uses

- This product can be used for any area that requires high strength fixing.
- It is used for long-term rust-proofing, water-proofing and vibration-proofing of bridge, steel frame, steel metal, tank vessel pipe, railway, vehicle, container, refrigerator car, agricultural machine, transportation machine, building floor and concrete floor.

#### How to Use

- Stir CPU-700A(main agent) and CPU-700B(hardener) at 1:4(weight ratio) with hand mixing. Then pour it into necessary place.
- Because apparent death time is 30 minutes, use it within 30 minutes after mixing main agent:hardener.
- Limit one time mixing volume to 30 minute use-volume.
- Be careful to prevent water from flowing in the product.
- Seal the can if you do not use it. If water or air fills in CPU-700A(main agent) to harden it, it is impossible to use it. Be careful of sealing the can.
- Do not keep it in the place above 40°C for a long time

 **NABANG CNA CO., LTD.** 204, CHUPALSANDAN 1-GIL, PAENGSEONG-EUP, PYEONGTAEK-SI, GYEONGGI-DO 451-805  
KOREA  
Tel. 82-31-651-5911 / Fax. 82-31-691-6441, 82-31-658-6441